

SAFETY DATA SHEETS

According to the UN GHS revision 9

Version: 1.2
Creation Date: July 15, 2019
Revision Date: August 08, 2025

SECTION 1: Identification

1.1 GHS Product identifier

Product name Methanol

1.2 Other means of identification

Product number LCEM501467-EW
Other names -

1.3 Recommended use of the chemical and restrictions on use

Identified uses For laboratory and Industrial use only.
Uses advised against no data available

1.4 Supplier's details

Company CATO Research Chemicals Inc.
Address 3/F,Building B,No.179 BASIGO, Guangpu Rd East,Huangpu Dist,Guangzhou
Telephone +86-20-81960175

1.5 Emergency phone number

Emergency phone number +86-20-81960175
Service hours 'Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT +8 hours).

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Flammable liquids, Category 2

2.2 GHS label elements, including precautionary statements

Pictogram(s)



Signal word Danger
Hazard statement(s) H225 Highly flammable liquid and vapour

Precautionary statement(s)
Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

Response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P370+P378 In case of fire: Use ... to extinguish.

Storage
Disposal

P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards which do not result in classification

no data available

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Common names and synonyms	CAS number	EC number	Concentration
Ethanol	Ethanol	64-17-5	200-578-6	100%
Water	-	7732-18-5	-	-

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled

Fresh air, rest.

Following skin contact

Remove contaminated clothes. Rinse and then wash skin with water and soap.

Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

Following ingestion

Rinse mouth. Refer for medical attention.

4.2 Most important symptoms/effects, acute and delayed

Excerpt from ERG Guide 127 [Flammable Liquids (Water-Miscible)]: Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control may cause pollution. (ERG, 2016)

VAPOR: Irritating to eyes, nose and throat. LIQUID: Not harmful. (USCG, 1999)

SYMPTOMS: Symptoms of exposure to this compound may include irritation. Ingestion may result in mucous membrane irritation. Eye contact may cause immediate pain and conjunctival hyperemia, but no serious injury. ACUTE/CHRONIC HAZARDS: This compound may cause local irritation. It may also cause mucous membrane irritation. When heated to decomposition it emits acrid smoke and fumes. (NTP, 1992)

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Emergency and supportive measures: 1. Acute intoxication. Treatment is mainly supportive. a. Protect the airway to prevent aspiration and intubate and assist ventilation if needed. b. Give glucose and thiamine, and treat coma and seizures if they occur. Glucagon is not effective for alcohol-induced hypoglycemia. c. Correct hypothermia with gradual rewarming. d. Most patients will recover within 4-6 hours. Observe children until their blood alcohol level is below 50 mg/dL and there is no evidence of hypoglycemia. 2. Alcoholic ketoacidosis. Treat with volume replacement, thiamine, and supplemental glucose. Most patients recover rapidly. 3. Alcohol withdrawal. Treat with benzodiazepines.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

If material on fire or involved in fire: Do not extinguish fire unless flow can be stopped. Use water in flooding quantities as fog. Solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water. Apply water from as far a distance as possible. Use "alcohol" foam, dry chemical or carbon dioxide.

5.2 Specific hazards arising from the chemical

Excerpt from ERG Guide 127 [Flammable Liquids (Water-Miscible)]: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a (P) may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. (ERG, 2016) FLAMMABLE. Flashback along vapor trail may occur. Vapor may explode if ignited in an enclosed area. (USCG, 1999) This chemical is probably combustible. (NTP, 1992)

5.3 Special protective actions for fire-fighters

Use water spray, powder, alcohol-resistant foam, carbon dioxide. In case of fire: keep drums, etc., cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all ignition sources. Ventilation. Do NOT wash away into sewer. Collect leaking and spilled liquid in covered containers as far as possible. Absorb remaining liquid in inert absorbent. Wash away remainder with plenty of water. Store and dispose of according to local regulations.

6.2 Environmental precautions

Ventilation. Remove all ignition sources. Collect leaking and spilled liquid in sealable containers as far as possible. Wash away remainder with plenty of water.

6.3 Methods and materials for containment and cleaning up

Land spill: Apply appropriate foam to diminish vapor and fire hazard.

SECTION 7: Handling and storage

SECTION 7: Handling and storage

7.1 Precautions for safe handling

NO open flames, NO sparks and NO smoking. Closed system, ventilation, explosion-proof electrical equipment and lighting. Do NOT use compressed air for filling, discharging, or handling. NO contact with incompatible materials: See Chemical Dangers Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

7.2 Conditions for safe storage, including any incompatibilities

Fireproof. Separated from strong oxidants. Keep tightly closed, cool and away from flame.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure limit values

TLV: 1000 ppm as STEL; A3 (confirmed animal carcinogen with unknown relevance to humans). MAK: 380 mg/m³, 200 ppm; peak limitation category: II(4); carcinogen category: 5; pregnancy risk group: C; germ cell mutagen group: 5

Biological limit values

no data available

8.2 Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear safety goggles.

Skin protection

Protective clothing. Apron. Protective gloves.

Respiratory protection

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties and safety characteristics

Physical state	Liquid.
Colour	Colourless.
Odour	Mild, rather pleasant; like wine or whiskey
Melting point/freezing point	-114 °C. Atm. press.: 1 atm.
Boiling point or initial boiling point and boiling range	78.29 °C. Atm. press.: 1 013.25 hPa.
Flammability	Class IB Flammable Liquid: Fl.P. below 73 °F and BP at or above 100 °F.
Lower and upper explosion limit/flammability limit	Lower flammable limit: 3.3% by volume; Upper flammable limit: 19% by volume
Flash point	13 °C. Atm. press.: 1 atm.
Auto-ignition temperature	368.8 °C. Remarks: 368.8 +/- 7.4 °C.
Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	dynamic viscosity (in mPa s) = 1.17. Temperature: 20 °C. Remarks: Value attributed to Kirk Othmer.
Solubility	Miscible with water
Partition coefficient n-octanol/water	log Pow = -0.35. Temperature: 24 °C.
Vapour pressure	57.26 hPa. Temperature: 19.6 °C.
Density and/or relative density	786.4 kg/m ³ . Temperature: 25 °C.
Relative vapour density	1.59 (vs air)
Particle characteristics	no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

3300 ppm [Based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.]

Reacts slowly with calcium hypochlorite, silver oxide and ammonia. This generates fire and explosion hazard. Reacts violently with strong oxidants such as nitric acid, silver nitrate, mercuric nitrate and magnesium perchlorate. This generates fire and explosion hazard.

10.2 Chemical stability

no data available

10.3 Possibility of hazardous reactions

Flammable liquid when exposed to heat or flame .The vapour mixes well with air, explosive mixtures are easily formed.Acetyl chloride reacts violently with ethanol or water, [Rose, (1961)]. Acetyl bromide reacts violently with alcohols or water, [Merck 11th ed., 1989]. Mixtures of alcohols with concentrated sulfuric acid and strong hydrogen peroxide can cause explosions. Example: An explosion will occur if dimethylbenzylcarbinol is added to 90% hydrogen peroxide then acidified with concentrated sulfuric acid. Mixtures of ethyl alcohol with concentrated hydrogen peroxide form powerful explosives. Mixtures of hydrogen peroxide and 1-phenyl-2-methyl propyl alcohol tend to explode if acidified with 70% sulfuric acid, [Chem. Eng. News 45(43):73(1967); J. Org. Chem. 28:1893(1963)]. Alkyl hypochlorites are violently explosive. They are readily obtained by reacting hypochlorous acid and alcohols either in aqueous solution or mixed aqueous-carbon tetrachloride solutions. Chlorine plus alcohols would similarly yield alkyl hypochlorites. They decompose in the cold and explode on exposure to sunlight or heat. Tertiary hypochlorites are less unstable than secondary or primary hypochlorites, [NFPA 491 M, 1991]. Base-catalysed reactions of isocyanates with alcohols should be carried out in inert solvents. Such reactions in the absence of solvents often occur with explosive violence, [Wischmeyer(1969)].

10.4 Conditions to avoid

no data available

10.5 Incompatible materials

Many explosions have been experienced during the gravimetric determination of either perchlorates or potassium as potassium perchlorate by a standard method involving ethanol extraction. During subsequent heating, formation and explosion of ethyl perchlorate is very probable.

10.6 Hazardous decomposition products

no data available

SECTION 11: Toxicological information

Acute toxicity

- Oral: LD50 - rat (female) - 15 010 mg/kg bw.
- Inhalation: LC50 - mouse (male) - > 60 000 ppm.
- Dermal: no data available

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

A3; Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity

no data available

STOT-single exposure

The substance is severely irritating to the eyes. The vapour at high levels is irritating to the eyes and respiratory tract. The substance may cause effects on the central nervous system.

STOT-repeated exposure

The substance defats the skin, which may cause dryness or cracking. The substance may have effects on the upper respiratory tract and central nervous system. This may result in irritation, headache, fatigue and lack of concentration. See Notes.

Aspiration hazard

A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C.

SECTION 12: Ecological information

12.1 Toxicity

- Toxicity to fish: LC50 - Pimephales promelas - 14.2 g/L - 96 h.
- Toxicity to daphnia and other aquatic invertebrates: LC50 - Ceriodaphnia dubia - 5 012 mg/L - 48 h.
- Toxicity to algae: EC10 - Chlorella vulgaris - 86 mg/L - 4 d.
- Toxicity to microorganisms: IC50 - activated sludge from domestic and industrial sewage treatment plants - > 1 000 mg/L - 3 h.

12.2 Persistence and degradability

AEROBIC: Ethanol was shown to biodegrade under aerobic conditions in various screening tests using different types of inocula and incubation periods(1-7). 5 day theoretical BOD values range from 37% - 86%(1,4). Biodegradation of 3, 7, and 10 mg/L ethanol with filtered sewage seed in fresh water resulted in a 74% theoretical BOD in 5 days and 84% in 20 days; in salt water 45% of the theoretical BOD was reached in 5 days and 75% was reached in 20 days(4). Formaldehyde and acetic acid are products of biodegradation by a soil inoculum(6). Ethanol present at 100 mg/L, achieved 89% of its theoretical BOD using an activated sludge inoculum at 30 mg/L in the Japanese MITI test(7). Ethanol was rapidly degraded in aerobic microcosms prepared from low organic (0.2% organic carbon) sandy aquifer material obtained from Jurere Beach, Brazil(8). Microcosms were prepared with 20 grams of aquifer material and 50 mL of groundwater (pH 5.2). At a starting concentration of 100 mg/L, ethanol had half-lives of approximately 3 days in samples prepared with 20 mg/L of either benzene, toluene or o-xylene under aerobic conditions(8).

12.3 Bioaccumulative potential

An estimated BCF of 3 was calculated for ethanol(SRC), using a log Kow of -0.31(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

12.4 Mobility in soil

A log Koc of 0.44 has been reported for ethanol(2), corresponding to a Koc of 2.75(SRC). According to a classification scheme(2), this estimated Koc value suggests that ethanol is expected to have very high mobility in soil. Ethanol leaching was measured using a shallow sand and gravel test aquifer in Merrick Co, central Platte Valley, Nebraska which was subjected to a pulse containing 220 mg/L ethanol and 12 mg/L bromide and monitored for 2.5 months. Transport was not retarded. An average first-order decay constant was estimated of be 0.32/day, corresponding to a half-life of 2.2 days(3). A sorption coefficient on a snow surface was reported as log K = -3.04 (cu m snow surface/sq m air) at -6.8 deg C(4).

12.5 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

14.1 UN Number

ADR/RID: UN1170 (For reference only, please check.) IMDG: UN1170 (For reference only, please check.) IATA: UN1170 (For reference only, please check.)

14.2 UN Proper Shipping Name

ADR/RID: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (For reference only, please check.) IMDG: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (For reference only, please check.) IATA: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (For reference only, please check.)

14.3 Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.) IMDG: 3 (For reference only, please check.) IATA: 3 (For reference only, please check.)

14.4 Packing group, if applicable

ADR/RID: II (For reference only, please check.) IMDG: II (For reference only, please check.) IATA: II (For reference only, please check.)

14.5 Environmental hazards

ADR/RID: No

IMDG: No

IATA: No

14.6 Special precautions for user

no data available

14.7 Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Chemical name	Common names and synonyms	CAS number	EC number
Ethanol	Ethanol	64-17-5	200-578-6

European Inventory of Existing Commercial Chemical Substances (EINECS)	Listed.
EC Inventory	Listed.
United States Toxic Substances Control Act (TSCA) Inventory	Listed.
China Catalog of Hazardous chemicals 2015	Listed.
New Zealand Inventory of Chemicals (NZIoC)	Listed.
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	Listed.
Vietnam National Chemical Inventory	Listed.
Chinese Chemical Inventory of Existing Chemical Substances (China IECSC)	Listed.
Korea Existing Chemicals List (KECL)	Listed.

SECTION 16: Other information

Information on revision

Creation Date July 15, 2019
Revision Date August 08, 2025

Abbreviations and acronyms

- CAS: Chemical Abstracts Service
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transportation Association
- TWA: Time Weighted Average
- STEL: Short term exposure limit
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- EC50: Effective Concentration 50%

References

- IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en
- CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Other Information

Ethanol consumption during pregnancy may adversely affect the unborn child.Chronic ingestion of ethanol may cause liver cirrhosis and cancer.

Any questions regarding this SDS, Please send your inquiry to info@cato-chem.com

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any damage resulting from handling or from contact with the above product.